



# ITR-NVS5105EP

## H.265 1HDD 5ch PSE NVR



SILVER  
SERIES

### KEY FEATURES

#### HD Input

- Plug and play
- S+265/H.265/H.264 video formats
- Connectable to the third-party network cameras
- Up to 5-channel input
- 4 PoE ports
- Supports live view, storage, and playback of the connected camera at up to 8MP resolution

#### HD Output

- 1×HDMI and 1×VGA simultaneous outputs
- HDMI Video output at up to 4K (3840 × 2160) resolution

#### HD Storage

- 1 SATA interfaces, up to 10TB for each HDD
- S+265 compression effectively reduces the storage space and costs by up to 75%

#### HD Transmission

- 1×RJ45 self-adaptive 10/100 Mbps network interface
- PoE Port: 4×RJ45 self-adaptive 10/100 Mbps network interfaces

#### Various Applications


- Centralized management of IP cameras, including configuration, information import/export, real-time information display, upgrade, etc.
- Connectable to smart IP cameras from ITR and the recording, playing back, and backing up of VCA alarms can be realized
- VCA detection alarm is supported
- Smart search for the selected area in the video and smart playback to improve the playback efficiency
- Web6 supports plug-in-free browsing and can preview videos on all browsers
- Support cloud upgrade



## SPECIFICATIONS

<b>Input</b>	
Video Input	5-ch
Max Resolution	6MP
Two-way Audio Input	N/A
Bandwidth	Income 50Mbps; Outgoing 40Mbps
<b>Output</b>	
HDMI/VGA Output	HDMI 1-ch, 3840×2160, 1920×1080, 1440×900, 1366×768, 1280×800, 1280×720, 1024×768 VGA 1-ch, 1920×1080, 1440×900, 1366×768, 1280×800, 1280×720, 1024×768
Screen Split	1/3/4/6
Audio Output	1×RCA
<b>Decoding</b>	
Decoding Format	S+265/H.265/H.264
Recording Resolution	6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Preview Capability	6MP*1; 5MP*1; 4MP*1; 3MP*1; 1080P*4; 720P*5
Synchronous Playback	6MP*1; 5MP*1; 4MP*2; 3MP*2; 1080P*4; 720P*8
Records Encryption	Yes
<b>Hard Disk</b>	
SATA	1 SATA interface for 1 HDD
Capacity	Up to 10TB for each HDD
eSATA Interface	N/A
Array Type	N/A
<b>External Interface</b>	
Network Interface	1×RJ45 self-adaptive 10/100 Mbps network interface
USB Interface	2×USB 2.0
Serial Interface	N/A
Alarm In/Out	N/A
<b>Network</b>	
Protocol	P2P, IPV4, IPV6, DHCP, DDNS, NFS, NTP, HTTP, SMTP, SNMP, UPnP (Port Mapping), TCP, UDP, MULTICAST, RTSP, IPV4, IPV6, DDNS
System Compatibility	ONVIF (PROFILE S/T), SDK, P2P
<b>POE</b>	
POE Interface	4×RJ45 self-adaptive 10/100 Mbps network interface
Power per POE Port	30W
Max Current per POE Port	600mA
<b>General</b>	
Web Version	Web6
Language	Simplified Chinese, Traditional Chinese, English, Spanish, Italian, Korean, Turkish, Russian, Thai, French, Hebrew, Polish, Dutch, Farsi, Arabic, Vietnamese;
Operating Conditions	-10°C ~ 55°C, 10%~90% RH
Power Supply	DC48V, 1.35A
Consumption (without HDD)	≤65W (without HDD)
Chassis	1U
Dimensions	42.9×200×199.5mm, (1.69×7.87×7.85 inch)
Weight (without HDD)	0.4Kg (0.88lb)

### DIMENSIONS (Unit: mm)



### Physical Interfaces

